

Z Master® G3 Professional 6000, Model No. 75967 with MyRIDE™



TECHNICAL SPECIFICATIONS AND FEATURES

Engine	Kawasaki FX921V-ES04-R, 23.1 kW (31.0 hp), 999 cc, Carbureted V-twin cylinder.
Deck Size	152.4 cm (60.0 inches).
Deck Configuration	Right side discharge, three blade mid-mount rotary. Fabricated 7-gauge steel Turbo Force deck with welded reinforcements, mounting brackets, and gauge wheel brackets. The deck has three adjustable gauge wheels, and is suspended from the frame by four solid links. The deck has a no-tools adjustable discharge baffle.
Deck Spindles	2.54 cm (1.0 inch) diameter splined spindle shaft turning in greaseable ball bearings (up to MY2017), non-greaseable (from MY2017). Spindle housing is cast iron.
Height of Cut	2.5 cm to 14.0 cm (1.0 to 5.5 inches) with 6.4 mm (0.25 inch) increments. Foot operated lift assist.
Hydro Drive Unit	Twin Parker unitized 16 cc pump and 280.2 cc wheel motor assemblies. 1.6 litre integrated reservoir, spin on filter, cooling fans, internal shock valves and heavy duty components.
Ground Speed	18.5 km/h – forward max.
Steering Control	Ergonomic, adjustable steering levers with heavy duty dampeners.
Wheel Base	128.5 cm (50.6 inches) – Centre of castor to centre of drive tyre.
Width	134.6 cm (53.0 inches) – Outside of rear tyres.
Overall Width	192.3 cm (87.6 inches) – With the deflector down. 186.9 cm (73.6 inches) – With the deflector up (gate width).
Overall Length	218.7 cm (86.1 inches) – ROPS down.
Overall Height	179.1 cm (70.5 inches) – ROPS up.
Tyres	Front – 13 x 6.5 inch - 6, smooth tread, semi-pneumatic. Rear – 24 x 12.0 inch - 12 Turf Master.
Fuel Tank Capacity	45.4 litres.
Net Weight	575.6 kg (1269.0 lbs).
Folding ROPS	Standard.
Z-Stand	Optional.
Seat	Deluxe seat with large bolsters and thick cushion. Standard with pivotable armrests. The seat can pivot and hinge to allow for access underneath the seat. Four rubber mountings giving 3-D motion isolation.
Suspension	MyRIDE suspension system incorporating three adjustable coil over shock absorber assemblies allowing 9.1 cm (3.6 inches) of travel.
Armrests	Standard, pivotable.
Warranty	Machine 5 year / 1400 hour. Engine: 2 year engine warranty up to Sept 1, 2017. Machines retailed and registered from Sept. 1, 2017 have 3 year engine warranty. NOTE: Engine warranty is through Kawasaki USA, but administered by Toro Australia.

For additional technical and servicing information regarding this mower refer to Service Bulletin G3SB07/16, re-issued April 3, 2017.

ACCESSORIES AND ATTACHMENTS

Product	Part No. / Model No.
Hitch Kit	109-9487
Z-Stand Kit	121-4811
Light Kit	116-1154
Bimini Folding Sunshade	115-4510
Operator Discharge Chute Kit	117-3600
Roller Striper Kit	115-7470
Power Deck Lift Kit	132-5986
Filter Minder	99-4664
Anti-Scalp Kit (Trim Side)	108-4140
Toro Rider Arm Rest Bag	490-7320

Product	Part No. / Model No.
Recycler Kit	115-7468
E-Z Vac Blower and Drive Kit	78553
E-Z Vac Triple Soft Bagger	78563
E-Z Vac DFS Bagger	78567
Toro Rider Over Seat Bag	490-7317
Trash Holder Kit	TC26
Turbo Baffle Kit	107-1634
Spark Arrestor Screen	75-6880
Toro Deluxe Rider Cover	490-7319
Seat Cover	117-0095

REGULAR MAINTANENCE ITEMS

Product	Part No.
Air Cleaner Primary Element	119-5944
Air Cleaner Secondary Element	119-5945
Engine Oil Filter	49065-7010 or KW10761
Engine Fuel Filter	49019-0707
Spark Plugs	NGK BPR5ES
Transmission Oil Filter	117-0390 (2 required)

Product	Type / Capacity
Engine Oil Type	Detergent engine oil, API service SG, SH, SJ or higher. SAE 30 for normal conditions – otherwise refer to Operator's Manual.
Engine Oil Capacity	Without oil filter change – 1.7 litres With oil filter change – 1.9 litres
Transmission Oil	Toro Pro-Series HYPR-OIL 500 hydraulic oil.
Transmission Oil Capacity	Approximately 1.6 litres each side with filter change. Final check via dipstick.

Product	Part No.
Traction Drive Assembly Drive Belt	109-3388
Traction Drive Assembly Idler Pulley	109-8076
Traction Drive Assembly Engine Pulley	109-9905
PTO Clutch	126-4185
Deck Spindle Drive Belt	114-5858
Deck Spindle Assembly (Greaseable)	119-8560
Deck Spindle Assembly (Non-Greaseable)	127-0560
Deck Spindle Pulley	105-7734
Deck Spindle Drive Belt Flat Idler Pulley (MY2016)	116-4670
Deck Spindle Drive Belt Flanged Idler Pulley	116-4668
Deck Anti-Scalp Roller	1-603299
Deck Discharger Rubber Deflector	108-5029
Blade Attaching Screw	51-4060
Blade Attaching Screw Washer	103-0865
Fuel Tank Cap	126-1789
Front Castor Wheel & Axle Assembly	127-9528
Rear Tyre	1-633993
Ignition Key	63-8360
Battery	104-8162

MY2017	136-5404
--------	----------

Blade Types

60 in Blade Types	Part No.
High Flow (Standard)	105-7718-03
Low Flow (Sand and Leaves)	105-7716-03
Medium Flow (Bahai)	105-7715-03
Atomic	105-8777-03
Recycler	105-7777-03

60 in Blade Packs	Part No.
High Flow Blade 6 Pack	108-1114
Low Flow Blade 6 Pack	108-1128
Medium Flow Blade 6 Pack	108-1123
Atomic Blade 6 Pack	108-1115
Recycler Blade 6 Pack	110-0405